



African Continental Resources cc



LINK STICKS

Safe and efficient solutions for live working

36th
Anniversary
1989-2025

The Views, Founders Hill Office Park
18 Centenary Way, Founders Hill
2065

Tel : +27 11 608 1126 | Fax : +27 11 608 3313
info@acr.x.africa | www.acrx.africa

Insulated triangle telescopic hot stick




Tip section




Same grain as Hastings



Rubber lock



Locking button



End view
triangular shape

Note: fluorescent green tip section, highly visible, and a foam core

Features

Unique design: triangle pole. Each section can be quickly extended-retracted and fixed. No need to rotate the section to fix

High visibility: the tip section is fluorescent green, which is convenient for night operation and identification. The tip section is filled with fireproof and moisture-proof insulating foam to prevent the accumulation of water vapor

Easy operation: with a big size locking button, easy to operate even if wearing insulated gloves

Easy maintenance: smooth surface section, easy daily cleaning

Multifunctional: high strength aluminum alloy multi head, firmly connect with different tools

Multiple sizes: extended length from 3.8-12m, retracted length from 1.5-1.81m. Can be custom made according to customers' requirements


Pole: manufactured with epoxy reinforced fiberglass tubes, it fully complies with ASTM F1826 Standard. The surface grain of the fiberglass body is the same as Hastings, but with higher cost performance

Parameters	HIR-208	HIR-212	HIR-216	HIR-220	HIR-225	HIR-230	HIR-235	HIR-236	HIR-240
Extended	2.43m	3.8m	5m	6.43m	7.8m	9.21m	10.06m	10.6m	12m
Retracted	0.83m	1.48m	1.55m	1.62m	1.67m	1.72m	1.7m	1.77m	1.82m
Base Dia.	44.6mm	37mm	40.4mm	44.6mm	48.4mm	52.4mm	56.5mm	56.5mm	60.3mm
Weight	1.75kg	1.85kg	2.6kg	3.4kg	4.25kg	5.1kg	5.9kg	6.2kg	7.2kg
Sections	5	3	4	5	6	7	8	8	9
Case	C95	C160	C165	C175	C180	C180	C190	C190	C190


Insulated round telescopic hot stick




Rotatable
operating top




Top view
locking button



Tip section



Round tube



Rubber base

Features

High strength and high insulation: the pole is made of epoxy reinforced fiberglass, with high mechanical strength, light weight and good insulation

Unique design: round pole. Each section can be quickly extended-retracted and fixed

High visibility: the outer surface of the top rod section is fluorescent, which is convenient for night operation and identification. The top rod is optional filled with fireproof and moisture-proof insulating foam to prevent the accumulation of water vapor

Easy operation: with a locking button or rotating design, easy to operate even if wearing insulated gloves

Easy maintenance: smooth surface section, easy daily cleaning

Multifunctional: high strength aluminum alloy universal head, firmly connect with different tools

Multiple sizes: extended length from 1.8-12m. Can be custom made according to customers' requirements

Multiple color: yellow, orange and green color can be chosen

Parameters	SIR-1.8	SIR-3	SIR-4	SIR-5	SIR-6	SIR-7	SIR-9	SIR-10	SIR-12
Length	1.8m	3m	4m	5m	6m	7m	9m	10m	12m
Sections	2	3	3	4	4	5	6	8	8
Base Size	32mm	36mm	36mm	50mm	50mm	56mm	63mm	72mm	72mm

